



## ET-SBFMP10

ET-SBFMP10

<https://ap.pnd.panasonic.com/au/en/et-sbfmp10>

<b>Type</b>	Function board-type (Intel® SDM standard SLOT-compatible)
<b>Terminals -&gt; HDMI™ IN</b>	—
<b>Terminals -&gt; HDMI™ OUT</b>	—
<b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>	3.5 mm stereo mini-jack
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T,NDI® and Dante® (2 channels)* <sup>1</sup> compatible
<b>Video format</b>	H.264, 8-bit, 3840 x 2160 pixels, 60p, YPbPr 4:2:0, 300 Mbps /H.265, 8-bit, 18 million pixels (long side 7680 pixels or less),60p, (including 7680 x 1920/60p, 4096 x 4096/60p), YPbPr 4:2:0, 300 Mbps
<b>Max. video output resolution</b>	3840 x 2160/60p
<b>Audio format</b>	AAC-LC, 16-bit, stereo
<b>Storage</b>	512 GB* <sup>4</sup>
<b>Operating system</b>	Linux®
<b>Power supply</b>	—
<b>Maximum power consumption</b>	—
<b>Dimensions (W x H x D)</b>	Approx. 195 x 25 x 123.2 mm (7 11/16" x 1" x 4 27/32")
<b>Weight</b>	Approx. 0.26 kg (0.57 lbs)
<b>ENVIRONMENT -&gt; Operating Environment(Temperature)</b>	0-45 °C (32-113 °F) * <sup>5</sup>
<b>ENVIRONMENT -&gt; Operating Environment(Humidity) (No condensation)</b>	10-80 % (no condensation)
<b>Footnote Description</b>	<ol style="list-style-type: none"> <li>1. HAP Q content is not supported.</li> <li>2. When four HDMI™ outputs are used simultaneously.</li> <li>3. Compatible with HAP 1 and HAP Q. Please consult the spec file for detailed information.</li> <li>4. For the ET-FMP20 (512 GB) and ET-SBFMP10 (512 GB), approximately 30 GB of the total storage space is allocated for system usage and is unavailable to the user.</li> <li>5. The operating temperature range may differ according to the specific projector model paired with the ET-SBFMP10.</li> </ol>