

Panasonic



5,200 LM PT-FRQ50 1-chip DLP™ 4K

PT-FRQ50

1- DLP™

Key Features

1- DLP™ , 5,200lm

4K (3840 x 2160)

2.0 V/H (V: +71 %, -48 %, H: +34 %, -27%)

Geometry Manager Pro

- 240Hz/1080p



MEVIX



Dimensions -> Depth (not including protruding parts)	492 mm (19 3/8")
Weight *16	16.1 kg (35.5 lbs)
Operating environment -> Operating temperature *17 *18	0-45 °C (32-113 °F)
Operating Environment -> Operating humidity (No condensation)	10-80 % (no condensation)
Applicable software	, Early Warning Software
NFC	No
Control function via LAN	Crestron Connected™ V2, Crestron XiO Cloud™*12, Art-Net DMX, AMX® DD, PJLink™ (Class 2)
Terminals -> SDI IN	—
Terminals -> DVI-D IN	—
Terminals -> DisplayPort™ IN	—
Gross Dimensions (W x H x D in mm)	FRQ60W/FRQ60B/FRQ60BD8: 684 x 291 x 596 mm FRQ60WEJ/FRQ60BEJ: 694 x 310 x 606 mm
Gross Weight (Kg)	FRQ60W/FRQ60B: 20.9 kg (46.0 lbs) FRQ60WEJ/FRQ60BEJ: 22.4 kg (49.4 lbs) FRQ60BD8: 20.2 kg (44.5 lbs)
Active 3D	No
SDM	No
EAN	PT-FRQ60W: 5025232923021 PT-FRQ60WEJ: 5025232923014 PT-FRQ60B: 5025232922994 PT-FRQ60BEJ: 5025232923007 PT-FRQ60BD8: 8887549898655
Footnote Description	<p>1. 120Hz/240Hz가</p> <p>2. [PICTURE MODE]가 [DYNAMIC], DAY LIGHT VIEW]가 [OFF], [DYNAMIC CONTRAST]가 [OFF], [LIGHT OUTPUT] [100%], [AUTO POWER SAVE] [OFF]</p> <p>3. , , ISO/IEC 21118: 2020</p> <p>4. , , (American National Standards Institute)</p> <p>5.</p> <p>6. ((PICTURE MODE): [DYNAMIC], [DYNAMIC CONTRAST] , 30 °C [86 °F], 700 m [2,297 ft], 0.15 mg/m3). 50 %</p> <p>7. 4K/60p</p> <p>8. 4K/60p . YPBPR 4:2:0</p> <p>9. 3.00 . AJ-WM50 IPv6</p> <p>10.</p> <p>11.</p> <p>12. 2,700m(8,858) , 35 °C(95 °F) ,</p> <p>13. 3.00 . AJ-WM50 0-40 °C(32-104 °F)가</p>