

Panasonic



가 Native 4K 50,000lm

PT-RQ50K

50,000 lm 4K(4096 × 2160) 3-Chip DLPTM

. () 52 dB . Intel® SDM / SLOT NX

NFC Smart Projector Control .

. . 24 365 360°

. 130 kg, 720 × 445 × 1,070 mm.

: black.

Key Features

- 3 DLP, 50,000lm, Native 4K
- 20,000
- 20,000:1 ...





PT-RQ50K

<https://ap.pnd.panasonic.com/id/ko/products/projectors/pt-rq50k>

Projector type	3-Chip DLP™ projector
Display method	DLP™ x 3, DLP™ ◆ ◆
Display Device -> Panel size	35.1 mm (1.38 in) diagonal (17:9 aspect ratio)
Display Device -> Number of pixels	8,847,360 (4096 x 2160 pixels) x 3
Light source	Laser diodes (Blue LD, Red LD)
Light output *1 *2	50,000 lm
Light output (ANSI) *1 *3	50,000 lm
Light output (Center) *1 *4	51,000 lm (Center)
Time until light output declines to 50 %	20,000 [NORMAL] *5
Time until light output declines to 50 %	24,000 [ECO] *5
Resolution *6	Native 4K (4096 x 2160 pixels)
Contrast Ratio (typ.)	25,000:1 (Full On/Full Off, Dynamic Contrast [3])
Screen size (diagonal)	2.54–38.1 m (100–1,500 in) with new optional lens for PT-RQ50K, 17:9 aspect ratio
Center-to-corner zone ratio	90%
Lens	Optional (no lens included with this model)
Lens shift -> Vertical (from center of screen)	±45 % (±25 % with ET-D3QT600, ±30 % with ET-D3QT700/ET-D3QT800, ±40 % with ET-D3QW300) (powered)
Lens shift -> Horizontal (from center of screen)	±16 % (±8 % with ET-D3QT600, ±10 % with ET-D3QT700/ET-D3QT800, ±14 % with ET-D3QW300) (powered)
Keystone correction range	: ±40° (ET-D3QW300 ±28°), : ±40° (ET-D3QW300 ±15°)
Installation	/ 360°
Terminals -> MULTI PROJECTOR SYNC IN	BNC x 1
Terminals -> MULTI PROJECTOR SYNC OUT	BNC x 1
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals -> SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
Terminals -> REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
Terminals -> REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control
Terminals -> REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals -> DIGITAL LINK IN / LAN	RJ-45 x 1 for network and DIGITAL LINK connections (HDBaseT™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible
Terminals -> LAN	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
Terminals -> DC OUT	USB Connector (Type A) x 2 for power supply only (DC 5 V, total of 2 A)
Terminals -> USB TYPE A	USB connector (Type A) x 1 for optional Wireless Module (AJ-WM50 Series) / USB Memory Stick
Terminals -> SLOT	SLOT1 : Interface Board for 12G-SDI (ET-MDN12G10) suppliedSLOT2 : Optional interface boards, SLOT NX compatible
Power supply	AC 200–240 V, 50/60 Hz; AC 100–120 V, 50/60 Hz
Maximum power consumption *13	4,100 W (AC 100–120 V: 1,100 W)
On-mode power consumption (Operating mode) -> Normal *13 *14	3,970 W
On-mode power consumption (Operating mode) -> Eco *13 *14	3,110 W
Standby power consumption -> Normal	6 W
Cabinet materials	Fabricated metal and molded plastic
Filter *15	No
Operation noise -> Normal	52 dB [NORMAL]
Body Colour	Black
Dimensions (W x H x D)	720 × 445 × 1,070 mm (28 11/32" × 17 17/32" × 42 1/8") (,)
Gross Dimensions (W x H x D in mm)	1021 x 731 x 1499 mm
Weight *16	126 kg (278 lbs) ()
Gross Weight (Kg)	RQ50KE/RQ50KE: 155.2 kg (342.1 lbs)
Operating environment -> Operating temperature *17 *18	0–45 °C (32–113 °F)
Operating Environment -> Operating humidity (No condensation)	10–80 % (no condensation)
Applicable software	, , Geometry Manager Pro, iOS/Android ™
NFC	Yes
EAN	RQ50KE: 5025232911301 RQ50KE: 8887549774911

Terminals -> SDI IN	—
Terminals -> HDMI™ IN	—
Terminals -> DVI-D IN	—
Terminals -> DisplayPort™ IN	—
Active 3D	No
SDM	No
Front URL	https://eu.connect.panasonic.com/gb/en/projectors/pt-rq50k
Footnote Description	1. [OPERATING MODE]가 [NORMAL] . 2. , , ISO/IEC 21118: 2020 . 3. , (American National Standards Institute) . 4. 5. 50% . IEC62087: 2008 , NORMAL , [3], 35 °C(95 °F), 700m(2,297 ft), 0.15 mg/m3 50 % 6. 7. 1,400 m(4,593 ft)~4,200 m(13,780 ft) , 0 °C(32 °F)~40 °C(104 °F) . 8. AJ-WM50 , 0~40 °C(32~104 °F) . 9. 2,700m(8,858) , 30 °C(86 °F) , . 2,700m(8,858) 4,200m(13,780) , 25°C(77°F) ,