



Providing a more realistic feeling with the 360-degree camera speakerphone

## PressIT360 - 360 degree video conferencing

PressIT360 is the all-in-one web conference system with high-performance 360-degree camera, mic and speakers, supporting a hybrid working environment that connects online and offline.

### Key Features

---

Optimal Video and Audio Transmission

---

Simple Operation

---

Installation and Portability



## PressIT360 - 360 degree video conferencing

<https://ap.pnd.panasonic.com/in/en/pressit360-360-degree-video-conferencing>

<b>CAMERA -&gt; Camera sensor</b>	1/2.7" 5MP CMOS
<b>CAMERA -&gt; Shooting pixels</b>	2560 × 1440 × 4
<b>CAMERA -&gt; Viewing angle</b>	360 (H) × 60 (V)
<b>CAMERA -&gt; Camera units</b>	4
<b>CAMERA -&gt; Lens FOV (Field of view)</b>	140 (D) / 140 (H) / 103 (V)
<b>CAMERA -&gt; F number of the lens</b>	2.5
<b>CAMERA -&gt; Lens TTL</b>	14.7 mm (0.58")
<b>CAMERA -&gt; Opt Distortion</b>	
<b>CAMERA -&gt; USB video format</b>	UVC 1.5 1280 × 720 @ 30fps, 1920 × 1080 @ 30fps Motion JPEG
<b>MIC -&gt; Microphone</b>	MEMS Microphone array
<b>MIC -&gt; MIC units</b>	7
<b>MIC -&gt; Beam forming</b>	Supported
<b>MIC -&gt; MIC sensitivity</b>	-35 dBFS
<b>MIC -&gt; SN ratio</b>	68.75 dBA
<b>MIC -&gt; MIC pick up distance</b>	Up to 5 m (16.4 ft)
<b>MIC -&gt; Noise canceling</b>	AEC/AGC/DNR/Keyboard noise suppression
<b>SPEAKER -&gt; Speaker out</b>	1.5 W (When supplying power from USB Type-C) or 3 W (When AC adaptor is connected)
<b>SPEAKER -&gt; USB sound format</b>	UAC Revision 1.0
<b>TERMINALS -&gt; USB</b>	USB Type-C (USB2.0)
<b>TERMINALS</b>	DC plug
<b>ELECTRICAL -&gt; Power</b>	USB Type-C (5 V/3 A) or AC adaptor DC 12 V/2 A
<b>ELECTRICAL -&gt; Power consumption (when outputting video)</b>	11 W
<b>ELECTRICAL -&gt; Dimension (Height)</b>	φ 64 mm (2.52")(Operation base φ 100 mm (3.94"))
<b>MECHANICAL -&gt; Dimension (Diameter)</b>	285 mm (11.23")
<b>MECHANICAL -&gt; Weight</b>	Approx. 950 g(2.1 lbs)
<b>MECHANICAL -&gt; Color</b>	black
<b>MECHANICAL -&gt; Security slot</b>	Noble Wedge lock (with mounting surfaces of 11 mm φ or less.)
<b>ENVIRONMENTAL -&gt; Operating Environment(Temperature)</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>ENVIRONMENTAL -&gt; Operating Environment(Humidity)</b>	20% to 80% (Non condensation)
<b>ENVIRONMENTAL -&gt; Usable altitude range</b>	0 m to 2800 m / 0 ft to 9186 ft
<b>UPC Code</b>	885170391277
<b>Features -&gt; Video display modes (View)</b>	Single / Dual / Multi / Surround / Stable
<b>Features -&gt; The operation of button</b>	Changing Mode / Adjustment of volume / Audio mute
<b>Features -&gt; Application</b>	PressIT360 application Support OS : Microsoft Windows (Windows 10/Windows 11), / macOS