Panasonic CONNECT

Zoom lens for PT-MZ16K/PT-MZ13K/PT-MZ10K

ET-EMU100

Throw Ratio 0.330 – 0.353:1 (Aspect 16:10)0.329 – 0.353:1 (Aspect 16:9)0.396 – 0.425:1 (Aspect 4:3)

Key Features

- Ultra-Short-Throw Versatility with Zero Offset
- Flexibility Streamlines Installation Workflow
- Durability for Peace of Mind

Panasonic CONNECT

ET-EMU100

https://ap.pnd.panasonic.com/kr/en/et-emu100

Lens type	Ultra-Short-Throw Zoom Lens
F-number	1.9
Focal length (f)	7.23 mm - 7.73 mm [9/32 - 5/16"]
Screen size	100–400 inches
Throw ratio -> WUXGA	0.330 - 0.353:1
Throw ratio -> WXGA	0.330 - 0.353:1
Throw ratio -> XGA	0.396 - 0.425:1
Lens-shift -> Vertical	PT-MZ16K/PT-MZ13K/PT-MZ10K : +50 % – -20 % *1
Lens-shift -> Horizontal	PT-MZ16K/PT-MZ13K/PT-MZ10K : ±20 % *1
Zoom	x1.07
Dimensions -> (W)	200 mm (7 7/8″)
Dimensions -> (H)	200 mm (7 7/8″)
Dimensions -> (D)	509 mm (20 1/32″)
Dimensions(WxHxD)	200 × 200 × 509 mm (7-7/8 × 7-7/8 × 20-1/32")
Weight	7.20 kg (15.87 lbs)
Applicable projectors	PT-MZ16KL/PT-MZ13KL/PT-MZ10KL
Footnote Description	* When PT-RQ50K's handle is attached, vertical lens-shift range is -8 % – +50 %. Vertical lens-shift range is -50 % – +50 % with PT-RQ50K's supplied handle removed. Please refer to instruction guide for details on how to remove the handle.