



Zero Offset Ultra Short Throw Zoom Lens

ET-DLE020 (for 1-Chip DLP™ Laser Projectors)

Key Features

Superior Flexibility for Easy Installation

Fits Easily in Tight Exhibition Spaces

High Reliability for Continuous Operation

On-Axis Rear Projection

Zero Offset and Flexible Setup for Multi-Screen Projection

ET-DLE020 (for 1-
Chip DLP™ Laser
Projectors)

<https://ap.pnd.panasonic.com/kr/en/et-dle020for-1-chip-dlptm-laser-projectors>

| | |
|------------------------------------|---|
| Lens type | Ultra-Short-Throw Zoom Lens |
| F-number | 2 |
| Focal length (f) | 4.1-4.4 mm (5/32-11/64") |
| Screen size | 100-400 inches |
| Throw ratio -> 4K | 0.279-0.297:1 |
| Throw ratio -> WUXGA | 0.280-0.299:1 |
| Throw ratio -> WXGA | 0.294-0.314:1 |
| Throw ratio -> XGA | 0.290-0.309:1 |
| Lens-shift -> Vertical | +50 % - -16 % |
| Lens-shift -> Horizontal | +10 % - -20 % |
| Zoom | Yes |
| Dimensions -> (W) | 170 mm (6 11/16") |
| Dimensions -> (H) | 170 mm (6 11/16") |
| Dimensions -> (D) | 391 mm (15 13/32") |
| Dimensions(WxHxD) | 170 × 170 × 391 mm (6-11/16 × 6-11/16 × 15-13/32") |
| Weight | Approx. 3.2 kg (7.05 lbs) |
| Applicable projectors | PT-RQ7L / PT-RQ6L / PT-RZ7L / PT-RZ6L / PT-RZ990 / PT-RZ890 / PT-RZ790 / PT-RZ690 / PT-RCQ10 / PT-RCQ80 / PT-RZ120 / PT-RZ970 / PT-RW930 / PT-RX110 / PT-RZ870 / PT-RZ770 / PT-RW730 / PT-RZ660 / PT-RW620 |

Footnote Description

1. Value is for ceiling installations at WUXGA resolution. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value.
2. The lens fixed attachment included with the ET-DLE020 cannot be attached to the RQ7 Series. When using the ET-DLE020, the included bracket is not required. Other compatible projector models require the Lens Fixed Attachment bracket.