

# Panasonic



AC 100-240 V  
가

15,000lm

1-Chip DLP™

## PT-REQ15

PT-REQ15 1-Chip DLP™ 4K  
240 Hz

15,000lm 4K

가

Key Features

---

---

---



MEVIX



<b>Projector type</b>	1-Chip DLP™ projector
<b>Display method</b>	DLP™ chip x 1, DLP™ projection system
<b>Display Device -&gt; Panel size</b>	0.8 in. diagonal (16:10 aspect ratio)
<b>Display Device -&gt; Number of pixels</b>	2,304,000 (1920 x 1200 pixels)
<b>Light source</b>	Laser diode
<b>Light output *1 *2</b>	15,000 lm
<b>Light output (ANSI) *1 *3</b>	15,000 lm
<b>Light output (Center) *1 *4</b>	15,500 lm (Center)
<b>Time until light output declines to 50 % -&gt; NORMAL *5</b>	20,000 hours [NORMAL]
<b>Time until light output declines to 50 % -&gt; ECO *5</b>	24,000 hours [ECO]
<b>Time until light output declines to 50 % -&gt; QUIET *5</b>	20,000 hours [QUIET]
<b>Resolution</b>	4K (3840 x 2400 pixels) (Quad Pixel Drive: ON)
<b>Contrast Ratio (typ.) *2</b>	25,000:1 (Full On/Full Off, Dynamic Contrast [3])
<b>Screen size (diagonal)</b>	70–700 inches (with supplied lens)
<b>Center-to-corner zone ratio *2</b>	90%
<b>Lens</b>	Optional powered zoom/focus lenses
<b>Lens shift -&gt; Vertical(from center of screen)</b>	±60 % (with ET-C1W400/W500/S600/T700), ±50 % (with ET-C1W300/U100)
<b>Lens shift -&gt; Horizontal(from center of screen)</b>	±29 % (with ET-C1W400/W500/S600/T700), ±23 % (with ET-C1W300/U100)
<b>Keystone correction range</b>	Vertical: ±40 ° (±5 ° with ET-C1U100; ±10 ° with ET-C1W300; ±16 ° with ET-C1W400; ±22 ° with ET-C1W500)Horizontal: ±40 ° (±3 ° with ET-C1U100; ±5 ° with ET-C1W300; ±10 ° with ET-C1W400; ±15 ° with ET-C1W500)
<b>Installation</b>	Ceiling/floor, front/rear, free 360-degree installation
<b>Terminals -&gt; HDMI™ IN</b>	HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input)
<b>Terminals -&gt; DisplayPort™ IN</b>	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input)
<b>Terminals -&gt; MULTI PROJECTOR SYNC IN</b>	BNC x 1
<b>Terminals -&gt; MULTI PROJECTOR SYNC OUT</b>	BNC x 1
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals -&gt; SERIAL OUT</b>	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
<b>Terminals -&gt; REMOTE 1 IN</b>	M3 stereo mini-jack x 1 for wired remote control
<b>Terminals -&gt; REMOTE 1 OUT</b>	M3 stereo mini-jack x 1 for link control (for wired remote control)
<b>Terminals -&gt; REMOTE 2 IN</b>	D-sub 9-pin (female) x 1 for external control (parallel)
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
<b>Terminals -&gt; DC OUT</b>	USB Type A x 1 (for power supply, DC 5 V, 2 A)
<b>Terminals -&gt; USB TYPE A</b>	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory
<b>Terminals -&gt; SLOT</b>	Open slot for function boards, Intel® SDM standard-compatible
<b>Protocol versions</b>	IPv4, IPv6*5
<b>Power supply</b>	AC 100–240 V, 50/60 Hz
<b>Maximum power consumption *13</b>	1,140 W (11.5–4.7 A) (1,150 VA)(Power consumption is 1,090 W at AC 200–240 V)
<b>On-mode power consumption(Operating mode) -&gt; Normal *13</b>	[NORMAL] 985 W (AC 100–120 V), 940 W (AC 200–240 V)
<b>On-mode power consumption(Operating mode) -&gt; Eco *13</b>	[ECO] 765W (AC 100–120 V), 735 W (AC 200–240 V)
<b>On-mode power consumption(Operating mode) -&gt; Quiet *13</b>	[QUIET] 760 W (AC 100–120 V), 730 W (AC 200–240 V)
<b>Cabinet materials</b>	Molded plastic
<b>Filter *14</b>	No
<b>Operation noise -&gt; Normal</b>	42 dB [NORMAL]
<b>Operation noise -&gt; Eco</b>	42 dB [ECO]
<b>Operation noise -&gt; Quiet</b>	38 dB [QUIET]
<b>Body Colour</b>	Black
<b>Dimensions (W x H x D)</b>	PT-REQ15: 498 x 212 x 648 mm (19 19/32" x 8 11/32" x 25 1/2") (With feet at shortest position)PT-REQ15L: 498 x 212 x 538 mm (19 19/32" x 8 11/32" x 21 3/16") (With feet at shortest position)
<b>Dimensions (W x H x D) -&gt; Width (not including protruding parts)</b>	498 mm (19 19/32")
<b>Dimensions -&gt; Height (including protruding parts)</b>	212 mm (8 11/32")
<b>Dimensions -&gt; Depth (not including protruding parts)</b>	538 mm (21 3/16")
<b>Gross Dimensions (W x H x D in mm)</b>	REQ15LBU/REQ15LBUG/REQ15BU: 655 x 849 x 378 mm REQ15LBEJ: 651 x 838 x 375 mm REQ15LBE/REQ15BE: 639 x 826 x 355 mm
<b>Weight *15</b>	PT-REQ15: Approx. 28.7 kg (63.27 lbs)(with supplied lens)PT-REQ15L: Approx. 27.0 kg (59.52 lbs)(without lens)

<b>Gross Weight (Kg)</b>	REQ15LBU/REQ15LBUG: 33.1 kg (73.1 lbs) REQ15LBEJ: 35.3 kg (77.8 lbs) REQ15LBE: 33.2 kg (73.1 lbs) REQ15BU: 34.8 kg (76.8 lbs) REQ15BEJ: 37.0 kg (81.5 lbs) REQ15BE: 34.9 kg (76.9 lbs)
<b>Operating environment -&gt; Operating temperature *16 *17</b>	0-45 °C (32-113 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	10-80 % (no condensation)
<b>Applicable software</b>	Multi Monitoring & Control Software, Projector Network Setup Software, Real-Time Tracking Projection-Mapping System, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™
<b>NFC</b>	<a href="https://docs.connect.panasonic.com/projector/products/smartycontrol/regional.html#regional">https://docs.connect.panasonic.com/projector/products/smartycontrol/regional.html#regional</a>
<b>Control function via LAN</b>	Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net DMX, AMX® DD, and PJLink™ (Class 2)
<b>EAN</b>	REQ15LBEJ: 5025232960910 REQ15LBE: 8887549861116 REQ15BEJ: 5025232960927 REQ15BE: 8887549861147
<b>Terminals -&gt; SDI IN</b>	—
<b>Terminals -&gt; DVI-D IN</b>	—
<b>Terminals -&gt; DIGITAL LINK IN / LAN</b>	—
<b>Active 3D</b>	No
<b>SDM</b>	Yes
<b>Footnote Description</b>	<ol style="list-style-type: none"> <li>1. ( : ET-C1S600)가</li> <li>2. [OPERATING MODE]가 [NORMAL]</li> <li>3. , , ISO/IEC 21118: 2020</li> <li>4. , , (American National Standards Institute)</li> <li>5.</li> <li>6. 50% . IEC62087: 2008 Broadcast Contents, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of airborne particulate matter. 50%</li> <li>7. AJ-WM50 IPv6</li> <li>8. , , ISO/IEC 21118: 2020 700m(2,297 ) 25°C(77°F)</li> <li>9. 80 W</li> <li>10.</li> <li>11. AJ-WM50 , 0-40 °C(32-104 °F) 1,400 m(4,593 ft)-4,200 m(13,780 ft) , 0 °C(32 °F)-40 °C(104 °F)</li> <li>12. REQ15 Web Control UI</li> </ol>