

Panasonic



1-Chip DLP™

PT-REZ10

10,000lm WUXGA 1-Chip DLP™

Key Features





PT-REZ10

<https://ap.pnd.panasonic.com/kr/ko/PT-REZ10>

Projector type	1- DLP™
Display method	DLP™ x 1, DLP™ ◆ ◆
Display Device -> Panel size	0.8 in diagonal (16:10 aspect ratio)
Display Device -> Number of pixels	2,304,000 (1920 x 1200 pixels)
Light source	Laser diode
Light output *1 *2 *3	10,000 lm
Light output (ANSI) *1 *2 *4	10,000 lm
Light output (Center) *1 *2 *5	10,300 lm (Center)
Time until light output declines to 50 % *20,000 [NORMAL]	-> NORMAL *6
Time until light output declines to 50 % *24,000 [ECO]	-> ECO *6
Time until light output declines to 50 % *20,000 hours [QUIET]	-> QUIET *5
Resolution	WUXGA (1920 x 1200 pixels)
Contrast Ratio (typ.) *3	25,000:1 (Full On/Full Off, Dynamic Contrast [3])
Screen size (diagonal)	70-700 inches (with supplied lens)
Center-to-corner zone ratio *3	90%
Lens	Powered zoom (throw ratio 1.36-2.10:1 for supplied lens), powered focus
Lens shift -> Vertical (from center of screen)	±60 % (with ET-C1W400/W500/S600/T700), ±50 % (with ET-C1W300/U100)
Lens shift -> Horizontal (from center of screen)	±29 % (with ET-C1W400/W500/S600/T700), ±23 % (with ET-C1W300/U100)
Keystone correction range	Vertical: ±40 ° (±5 ° with ET-C1U100; ±10 ° with ET-C1W300; ±16 ° with ET-C1W400; ±22 ° with ET-C1W500), Horizontal: ±40 ° (±3 ° with ET-C1U100; ±5 ° with ET-C1W300; ±10 ° with ET-C1W400; ±15 ° with ET-C1W500)
Installation	/ , / , 360
Terminals -> HDMI™ IN	HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input)*5
Terminals -> DisplayPort™ IN	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input)*5
Terminals -> MULTI PROJECTOR SYNC IN	BNC x 1
Terminals -> MULTI PROJECTOR SYNC OUT	BNC x 1
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals -> SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
Terminals -> REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
Terminals -> REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)
Terminals -> REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals -> LAN	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
Terminals -> DC OUT	USB Type A x 1 (for power supply, DC 5 V, 2 A)
Terminals -> USB TYPE A	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory
Terminals -> SLOT	Open slot for function boards, Intel® SDM compatible
Protocol versions	IPv4, IPv6*6
Power supply	AC 100-240 V, 50/60 Hz
Maximum power consumption *9	840 W (8.8-3.7 A) (850 VA) (Power consumption is 810 W at AC 200-240 V)
On-mode power consumption (Operating mode) -> Normal *9 *9 *10	[NORMAL] 700 W (AC 100-120 V), 675 W (AC 200-240 V)
On-mode power consumption (Operating mode) -> Eco *9 *9 *10	[ECO] 540 W (AC 100-120 V), 525 W (AC 200-240 V)
On-mode power consumption (Operating mode) -> Quiet *13 *14	[QUIET] 530 W (AC 100-120 V), 515 W (AC 200-240 V)
Cabinet materials	Molded plastic
Filter	No
Operation noise -> Normal *3	36 dB [NORMAL]
Operation noise -> Eco *3	36 dB [ECO]
Operation noise -> Quiet	33 dB [QUIET]
Body Colour	PT-REZ10LBEJ-BlackPT-REZ10LBE-BlackPT-REZ10BEJ-BlackPT-REZ10BE-BlackPT-REZ10LWEJ-WhitePT-REZ10LWE-WhitePT-REZ10WEJ-WhitePT-REZ10WE-White
Dimensions (W x H x D)	PT-REZ10: 498 x 212 x 648 mm (19 19/32" x 8 11/32" x 25 1/2") (With feet at shortest position)PT-REZ10L: 498 x 212 x 538 mm (19 19/32" x 8 11/32" x 21 3/16") (With feet at shortest position)
Dimensions (W x H x D) -> Width (not including protruding parts)	498 mm (19 19/32")

Dimensions -> Width (including protruding parts)	498 mm (19 19/32")
Dimensions -> Height (including protruding parts)	212 mm (8 11/32")
Dimensions -> Depth (not including protruding parts)	538 mm (21 3/16")
Dimensions -> Depth (including lens)	648 mm (25 1/2")
Gross Dimensions (W x H x D in mm)	REZ10BEJ/REZ10WEJ: Approx. 651 x 375 x 838 mm REZ10BE/REZ10WE: Approx. 639 x 355 x 826 mm
Weight *11	PT-REZ10: Approx. 28.7 kg (63.27 lbs) (with supplied lens)PT-REZ10L: Approx. 27.0 kg (59.52 lbs) (without lens)
Gross Weight (Kg)	REZ10BEJ/REZ10WEJ: 36.7 kg (81.0 lbs) REZ10BE/REZ10WE: 34.6 kg (76.4 lbs)
Operating environment -> Operating temperature *12	0–45 °C (32–113 °F)
Operating Environment -> Operating humidity (No condensation)	10–80 % (no condensation)
Applicable software	Logo Transfer Software*11, Multi Monitoring & Control Software, Projector Network Setup Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™
NFC	Yes
Control function via LAN	Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net DMX, AMX® DD, and PJLink™ (Class 2)
EAN	REZ10BEJ: 5025232951185 REZ10WEJ: 5025232951208 REZ10BE: 8887549850776 REZ10WE: 8887549850790
Terminals -> SDI IN	—
Terminals -> DVI-D IN	—
Terminals -> DIGITAL LINK IN / LAN	—
Active 3D	No
SDM	Yes
Footnote Description	<p>1. (: ET-C15600) .</p> <p>2. [OPERATING MODE]가 [NORMAL]</p> <p>3. , , ISO/IEC 21118: 2020 .</p> <p>4. , , (American National Standards Institute) .</p> <p>5. .</p> <p>6. 50% . IEC62087: 2008 Broadcast Contents, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of airborne particulate matter. 50%</p> <p>7. 4K WUXGA(1920 x 1200)</p> <p>8. AJ-WM50 IPv6</p> <p>9. , , ISO/IEC 21118: 2020 . ON 25 °C(77 °F), 700 m(2,297 ft)</p> <p>10. 80 W</p> <p>11. .</p> <p>12. AJ-WM50 , 0–40 °C(32–104 °F) . The operating environment temperature should be between 0 °C(32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).</p> <p>13. REZ15 Web Control UI</p>