

Panasonic



**World's Smallest and Lightest 8,000 lm*1 Projector
Enhances Communication in Brightly Lit Spaces**

PT-VMZ72

Introducing the VMZ82 Series: the world's smallest and lightest projector in its class¹, delivering up to 8,000 lm² for crisp, vibrant visuals in well-lit spaces. These intuitive LCD projectors integrate seamlessly into any layout, minimizing distractions while simplifying installation with exclusive features. With a stylish body containing recycled plastic and engineered for efficient, low-maintenance operation, the VMZ82 Series revitalizes communication quality in offices, classrooms, and beyond.

Key Features

Clear Projection Tailored to Your Space

Stress-Free Installation Flexibility

Efficient and Eco-Conscious Design

MEVIX



PT-VMZ72

<https://ap.pnd.panasonic.com/my/en/pt-vmz72>

| | |
|--|---|
| Projector type | LCD projectors |
| Display method | Transparent LCD panel (x 3, R/G/B) |
| Display Device -> Panel size | 16.3 mm (0.64 inch) (16:10 aspect ratio) |
| Display Device -> Number of pixels | 2,304,000 (1920 x 1200) pixels x 3 |
| Light source | Laser diodes |
| Light output *1 | VMZ82 : 8,000 lm*2 VMZ72 : 7,200 lm*2 VMZ62 : 6,500 lm*2 |
| Light output (ANSI) | VMZ82 : 8,000 lm (ANSI)*3 VMZ72 : 7,200 lm (ANSI)*3 VMZ62 : 6,500 lm (ANSI)*3 |
| Time until light output declines to 50 % | 20,000 hours [NORMAL] |
| -> NORMAL *3 | |
| Time until light output declines to 50 % | 24,000 hours [ECO] |
| -> ECO *3 | |
| Time until light output declines to 50 % | 20,000 hours [QUIET] |
| -> QUIET *6 | |
| Resolution | WUXGA (1920 x 1200 pixels) |
| Contrast Ratio (typ.) *1 | 5,000,000:1 (Full On/Full O) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].) |
| Screen size (diagonal) | 0.76–7.62 m (30–300 in), 16:10 aspect ratio |
| Center-to-corner zone ratio *1 | 85 % |
| Lens | 1.6x manual zoom (throw ratio: 1.09–1.77:1), manual focus lens, F=1.58–1.91, f=15.30–24.60 mm |
| Digital Zoom Extender *7 | Throw Ratio 1.09–2.21:1*6 (Corresponding value. When used together with optical zoom.) |
| Lens shift -> Vertical (from center of screen) *4 | +44 % |
| Lens shift -> Horizontal (from center of screen) *4 | ±20 % |
| Keystone correction range | Vertical ±25°, Horizontal ±35° |
| Terminals -> HDMI™ IN | HDMI™ 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/30p*8 signal input), CEC supported*9 |
| Terminals -> COMPUTER IN (D-SUB 15pin) | D-sub 15-pin (female) (RGB/YPbPr/YCbCr) |
| Terminals -> AUDIO IN (M3 Stereo Mini Jack) | M3 stereo mini-jack x 1 |
| Terminals -> AUDIO OUT (M3 Stereo Mini Jack) | M3 stereo mini-jack x 1 |
| Terminals -> SERIAL IN | D-sub 9-pin (female) x 1 for computer control (RS-232C compliant) |
| Terminals -> DIGITAL LINK IN / LAN | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBaseT™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], HDCP, Deep Color, 4K/30p*7 signal input) |
| Terminals -> LAN | RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PLink™ [Class 2] |
| Terminals -> USB TYPE A | USB Connector Type A x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A*9) |
| Protocol versions | IPv4, IPv6*10 |
| Power supply | AC 100–240 V, 50/60 Hz |
| Maximum power consumption | 345 W (3.6 A) (350 VA) (Power consumption is 335 W at 200–240 V) |
| On-mode power consumption (Operating mode) -> Normal | 310 W (100–240 V), 295 W (200–240 V) [NORMAL] |
| On-mode power consumption (Operating mode) -> Eco | 235 W (100–240 V), 225 W (200–240 V) [ECO] |
| On-mode power consumption (Operating mode) -> Quiet *9 *10 | 270 W (100–240 V), 260 W (200–240 V) [QUIET1] 230 W (100–240 V), 220 W (200–240 V) [QUIET2] |
| Built-in speaker | 10 W monaural |
| Cabinet materials | Molded plastic |
| Filter | Included |
| Estimated filter maintenance cycle | Approx. 20,000 hours |
| Operation noise -> Normal *1 | 37 dB [NORMAL] |
| Operation noise -> Eco *3 | 37 dB [ECO] |
| Operation noise -> Quiet *1 | 32 dB [QUIET1] 27 dB [QUIET2] |
| Dimensions (W x H x D) | 399 mm x 115 mm x 348 mm (15 23/32" x 4 17/32" x 13 11/16") (not including protruding parts) 399 mm x 133 mm x 348 mm (15 23/32" x 5 1/4" x 13 11/16") (with feet at shortest position) |

| | |
|---|--|
| Weight *7 | Approx. 7.0 kg (15.4 lbs) |
| Operating environment -> Operating temperature *8 *9 | 0–45 °C (32–113 °F)*14, *15 |
| Operating Environment -> Operating humidity (No condensation) | 20–80 % (no condensation) |
| Applicable software | Multi Monitoring & Control Software, Projector Network Setup Software, Presenter Light Software for Windows®*16, Wireless Projector App for iOS/Android™*17 |
| Terminals -> SDI IN | — |
| Terminals -> DVI-D IN | — |
| Terminals -> DisplayPort™ IN | — |
| Body Colour | PT-VMZ72-WhitePT-VMZ72EJ-WhitePT-VMZ72B-BlackPT-VMZ72BEJ-BlackPT-VMZ72J-WhitePT-VMZ72D8-White |
| Gross Dimensions (W x H x D in mm) | VMZ72/VMZ72B/VMZ72J/VMZ72D8: Approx. 538 x 260 x 466 mm VMZ72EJ/VMZ72BEJ: Approx. 546 x 276 x 474 mm |
| Gross Weight (Kg) | VMZ72/VMZ72B: 10.6 kg (23.4 lbs)VMZ72J: 9.8 kg (21.7 lbs)VMZ72D8: 11.5 kg (25.4 lbs)VMZ72EJ/VMZ72BEJ: 11.6 kg (25.6 lbs) |
| NFC | No |
| Active 3D | No |
| SDM | No |
| EAN | PT-VMZ72: 5025232969296 PT-VMZ72EJ: 5025232969289 PT-VMZ72B: 5025232969319 PT-VMZ72BEJ: 5025232969302 PT-VMZ72D8: 8887549898914 |
| Footnote Description | <ol style="list-style-type: none"> When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL]. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2]). Estimated time until light output declines to 50 % varies depending on environment. Resolution decreases when using Digital Zoom Extender. Grid Adjustment, 6-Point Screen Correction, V/H Keystone Correction, and curved-screen correction are not available when using this function. The range of corner adjustment is limited. When Digital Zoom Extender is set to 80 %. 4K signals are converted to the projector's resolution upon projection. Depending on the connected CEC command compatible device, the link control may not operate normally. On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready. The optional AJ-WM50 Series Wireless Module does not support IPv6. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). Filter cleaning cycle varies depending on the environment. The filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m3), 10,000 hours (under dust conditions of 0.15 mg/m3). Average value. May differ depending on the actual unit. Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level. When the optional AJ-WM50 Series Wireless Module is attached, the operating temperature range becomes 0–40 °C (32–104 °F). When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy while images and sound are being transmitted. When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800). |