



ET-SBFMP10

ET-SBFMP10

<https://ap.pnd.panasonic.com/nz/en/et-sbfmp10>

Type	Function board-type (Intel® SDM standard SLOT-compatible)
Terminals -> HDMI™ IN	—
Terminals -> HDMI™ OUT	—
Terminals -> AUDIO OUT(M3 Stereo Mini Jack)	3.5 mm stereo mini-jack
Terminals -> LAN	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T,NDI® and Dante® (2 channels)* ¹ compatible
Video format	H.264, 8-bit, 3840 x 2160 pixels, 60p, YPbPr 4:2:0, 300 Mbps /H.265, 8-bit, 18 million pixels (long side 7680 pixels or less),60p, (including 7680 x 1920/60p, 4096 x 4096/60p), YPbPr 4:2:0, 300 Mbps
Max. video output resolution	3840 x 2160/60p
Audio format	AAC-LC, 16-bit, stereo
Storage	512 GB* ⁴
Operating system	Linux®
Power supply	—
Maximum power consumption	—
Dimensions (W x H x D)	Approx. 195 x 25 x 123.2 mm (7 11/16" x 1" x 4 27/32")
Weight	Approx. 0.26 kg (0.57 lbs)
ENVIRONMENT -> Operating Environment(Temperature)	0-45 °C (32-113 °F) * ⁵
ENVIRONMENT -> Operating Environment(Humidity) (No condensation)	10-80 % (no condensation)
Footnote Description	<ol style="list-style-type: none"> 1. HAP Q content is not supported. 2. When four HDMI™ outputs are used simultaneously. 3. Compatible with HAP 1 and HAP Q. Please consult the spec file for detailed information. 4. For the ET-FMP20 (512 GB) and ET-SBFMP10 (512 GB), approximately 30 GB of the total storage space is allocated for system usage and is unavailable to the user. 5. The operating temperature range may differ according to the specific projector model paired with the ET-SBFMP10.