

Panasonic



가 가 20,000lm 1.3 DLP™ WUXGA 가

PT-RZ24K

가 가 20,000lm 1.3 DLP™ WUXGA 가

Key Features

Compact Form-Factor Streamlines Workflow

3-Chip DLP™ 4K Laser Projector with Quad Pixel Drive

20,000 Lumen Brightness



Body Colour	Black
Dimensions (W x H x D)	550 x 220 x 570 mm (21 5/8" x 8 11/16" x 22 7/16") ()
Dimensions (W x H x D) -> Width (not including protruding parts)	550 mm (21 5/8")
Dimensions -> Height (not including protruding parts)	220 mm (8 11/16")
Dimensions -> Depth (not including protruding parts)	570 mm (22 7/16")
Gross Dimensions (W x H x D in mm)	RZ24KU/RZ24KEJ: 792 x 794 x 455 mm RZ24KUY/RZ24KE: 770 x 772 x 445 mm
Weight *16	Approx. 35 kg (77.2 lbs)
Gross Weight (Kg)	RZ24KE: 42.4 kg (93.6 lbs) RZ24KEJ: 44.2 kg (97.5 lbs)
Operating environment -> Operating temperature *17 *18	0–45 °C (32–113 °F)
Operating Environment -> Operating humidity (No condensation)	10–80 % (no condensation)
Applicable software	Manager Pro, iOS/Android & TM, Geometry
NFC	Yes
EAN	RZ24KEJ: 5025232925544 RZ24KE: 8887549809767
Terminals -> SDI IN	—
Terminals -> DVI-D IN	—
Terminals -> DIGITAL LINK IN / LAN	—
Active 3D	Yes
SDM	Yes
Footnote Description	<p>1. (: ET-D3LES20) AC 200 V~AC 240 V</p> <p>2. [OPERATING MODE]† [NORMAL]</p> <p>3. , , ISO/IEC 21118: 2020</p> <p>4. , , (American National Standards Institute)</p> <p>5.</p> <p>6. 50% . IEC62087: 2008, NORMAL , [3], 35°C(95°F), 700m(2,297ft), 0.15 mg/m3 . 50%</p> <p>7. 4K PT-RZ24K PT-RZ17K WUXGA(1920 x 1200)</p> <p>8.</p> <p>9. , , ISO/IEC 21118: 2020 . ON 25 °C(77 °F), 700 m(2,297 ft)</p> <p>10.</p> <p>11. AJ-WM50 0–40 °C(32–104 °F) 1,400 m(4,593 ft)–4,200 m(13,780 ft) 0 °C(32 °F)–40 °C(104 °F)</p>