



Redefining Immersive Experiences with Rec. 2020 Color, 20,000 lm*1 Brightness, and Detailed 4K*2 Resolution

PT-HTQ20

Redefining Immersive Experiences with Rec. 2020 Color, 20,000 lm*1 Brightness, and Detailed 4K*2 Resolution *1 When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL]. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 Maximum physical resolution is 3840 x 2400 pixels with Quad Pixel Drive [ON].

Key Features

Immersive Visual Expression for Diverse Environments

Flexible Installation with Flagship Features

High Reliability for Demanding Applications



Projector type	1-Chip DLP™ RGB laser projector
Display method	DLP™ chip x 1, DLP™ projection system
Display Device -> Panel size	24.4 mm (0.96 in) diagonal (16:10 aspect ratio)
Display Device -> Number of pixels	2,304,000 pixels (1920 x 1200 dots)
Light source	Laser diodes (Red LD, Green LD, Blue LD)
Light output *1 *2	20,000 lm*3 (TBD)
Light output (ANSI) *3	20,000 lm*4 (TBD)
Light output (Center) *1 *2	20,400 lm*5 (TBD)
Time until light output declines to 50 %	20,000 hours [NORMAL]
-> NORMAL *4	
Time until light output declines to 50 %	24,000 hours [ECO]
-> ECO *4	
Resolution	4K (3840 x 2400 dots) (Quad Pixel Drive: ON)
Contrast Ratio (typ.) *2	25,000:1 (All white/All black, Dynamic Contrast [3]) (TBD)
Screen size (diagonal)	1.78-25.40 m (70-1000 in) (Depending on attached lens) (TBD)
Center-to-corner zone ratio *2	90 % or above
Lens	Optional (No lens included with this model)
Lens shift -> Vertical(from center of screen)	±55 % (Max, depending on attached lens) (TBD)
Lens shift -> Horizontal(from center of screen)	±20 % (Max, depending on attached lens) (TBD)
Keystone correction range	Vertical: ±55 % (Max, depending on attached lens) (TBD) Horizontal: ±20 % (Max, depending on attached lens) (TBD)
Installation	Ceiling/floor, front/rear, free 360-degree installation
Terminals -> SDI IN	12G/3G/HD-SDI signal compatible
Terminals -> HDMI™ IN	HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input)
Terminals -> MULTI PROJECTOR SYNC IN	BNC x 1, TTL high impedance
Terminals -> MULTI PROJECTOR SYNC OUT	BNC x 1, TTL output: Maximum 10 mA
Terminals -> SERIAL IN	D-sub 9-pin (Female) x 1 for external control (RS-232C compliant)
Terminals -> REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
Terminals -> REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (For wired remote control)
Terminals -> LAN	RJ-45 x 1 for network connection, PjLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
Terminals -> DC OUT	USB connector Type A x 1 for connecting optional AJ-WM50 Series Wireless Module/USB memory or for power supply (DC 5 V, 2 A)
Terminals -> SLOT	Slot x 1, open slot, for function boards, Intel® SDM standard-compatible
Protocol versions	IPv4, IPv6*7
Power supply	Single-phase AC 100-120 V / Single-phase AC 200-240 V, 50/60 Hz
Maximum power consumption *11	TBD
On-mode power consumption(Operating mode) -> Normal *11	TBD
On-mode power consumption(Operating mode) -> Eco *11	TBD
Cabinet materials	Molded plastic, processed metal parts
Operation noise -> Normal *2	TBD
Operation noise -> Eco *2	TBD
Operation noise -> Quiet *2	TBD
Dimensions (W x H x D)	Approx. 590 x 220 x 600 mm (23 7/32" x 8 21/32" x 23 5/8") (Excluding feet, protruding parts, and lens) (TBD)
Weight *7	Approx. 38 kg (83.8 lbs) or less (TBD)
Operating environment -> Operating temperature *8	0-45 °C (32-113 °F)*11(TBD)
Operating Environment -> Operating humidity (No condensation)	10-80 % (No condensation)(TBD)
Applicable software	Multi Monitoring and Control Software for Windows®, Visual Software Suite for Windows®, Projector Network Setup Software for Windows®, Smart Projector Control for iOS/Android™
Control function via LAN	Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net, AMX® DD, Extron® XTP12, and PjLink™ (Class 2)

Footnote Description

1. This is the value when the Zoom Lens (Model No.: ET-D3LES250) is used. The value varies depending on the lens.
2. When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL].
3. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped.
4. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.
5. Average light-output value of all shipped products measured at the center of screen in NORMAL Mode.
6. Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE] set to [DYNAMIC], [DYNAMIC CONTRAST] set to [3]). Estimated time until light output declines to 50 % varies depending on environment.
7. Optional AJ-WM50 Series Wireless Module is not compatible with IPv6.
8. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards.
9. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).
10. Average value. May differ depending on the actual unit.
11. The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft) above sea level. Note that altitude of 4,200 m (13,780 ft) above sea level is the maximum height that the performance of this projector is guaranteed. When using the projector at an altitude lower than 1,400 m (4,593 ft) above sea level, and the operating environment temperature becomes 35 °C (95 °F) or higher, the light output may be reduced to protect the projector. When using the projector at an altitude between 1,400 m (4,593 ft) and 2,700 m (8,858 ft), and the operating environment temperature becomes 30 °C (86 °F) or higher, the light output may be reduced to protect the projector. When using the projector at an altitude between 2,700 m (8,858 ft) and 4,200 m (13,780 ft), and the operating environment temperature becomes 25 °C (77 °F) or higher, the light output may be reduced to protect the projector (TBD). Do not use the projector in a location where the ambient temperature exceeds 40 °C (104 °F) regardless of the altitude when the optional AJ-WM50 Series Wireless Module is attached to the projector.
12. Only when optional TY-SB01 DL DIGITAL LINK Terminal Board is loaded.