



**Smooth and Detailed 4K\*1 Images from the  
Smallest, Lightest LCD Projector in Its Class\*2**

## PT-VMQ85

Smooth and Detailed 4K\*1 Images from the Smallest, Lightest LCD Projector in Its Class\*2 \*1 Displayed resolution (3840 x 2400 pixels) with 2-axis pixel-shifting technology [ON]. \*2 As of January 2026, according to our research, the PT-VMQ85 is the smallest and lightest 4K LCD projector with more than 8,000 lm, and the PT-VMQ75 is the smallest and lightest among those with more than 7,300 lm.

### Key Features

Making Immersive 4K\*1 Visuals More Accessible

Easy to Handle with Flexible Installation

Efficient, Eco-Conscious Design



PT-VMQ85

<https://ap.pnd.panasonic.com/ph/en/pt-vmq85>

<b>Projector type</b>	LCD projectors
<b>Display Device -&gt; Panel size</b>	0.64 inch (16:10 aspect ratio)
<b>Display Device -&gt; Drive method</b>	Transparent LCD panel (x 3, R/G/B)
<b>Display Device -&gt; Number of pixels</b>	2,304,000 (1920 x 1200) pixels x 3
<b>Light source</b>	Laser diodes
<b>Light output *1 *2</b>	8,000 lm
<b>Light output (ANSI) *1 *2</b>	8,000 lm
<b>Light output (Center) *1 *2</b>	8,400 lm
<b>Time until light output declines to 50 %</b>	20,000 hours [NORMAL]
<b>-&gt; NORMAL *6</b>	
<b>Time until light output declines to 50 %</b>	24,000 hours [ECO]
<b>-&gt; ECO *6</b>	
<b>Time until light output declines to 50 %</b>	20,000 hours [QUIET]
<b>-&gt; QUIET *6</b>	
<b>Resolution</b>	4K (3840 x 2400 pixels)*6
<b>Contrast Ratio (typ.) *3</b>	5,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)
<b>Screen size (diagonal)</b>	0.76–7.62 m (30–300 in), 16:10 aspect ratio
<b>Center-to-corner zone ratio *3</b>	85%
<b>Lens</b>	1.6x manual zoom (throw ratio: 1.09–1.77:1), manual focus lens, F=1.58–1.91, f=15.30–24.60 mm
<b>Digital Zoom Extender *7</b>	Throw Ratio 1.09–2.21:1*8 (Corresponding value. When used together with optical zoom.)
<b>Lens shift -&gt; Vertical(from center of screen)</b>	+44%
<b>Lens shift -&gt; Horizontal(from center of screen)</b>	±20 %
<b>Keystone correction range</b>	Vertical ±25 %, Horizontal ±35 %
<b>Installation</b>	Ceiling/floor, front/rear, free 360-degree installation
<b>Terminals -&gt; HDMI™ IN</b>	HDMI™ 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/60p signal input), CEC supported*9
<b>Terminals -&gt; HDMI™ OUT</b>	HDMI™ 19-pin x 1 (Compatible with HDCP, Deep Color, 4K/60p signal output)
<b>Terminals -&gt; AUDIO IN(M3 Stereo Mini Jack)</b>	M3 stereo mini-jack x 1
<b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>	M3 stereo mini-jack x 1
<b>Terminals -&gt; SERIAL IN</b>	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)
<b>Terminals -&gt; DIGITAL LINK IN / LAN</b>	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2],HDCP, Deep Color, 4K/60p*10 signal input)
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PLink™ [Class 2]
<b>Terminals -&gt; USB TYPE A</b>	USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A*11)
<b>Protocol versions</b>	IPv4, IPv6*12
<b>Power supply</b>	Single-phase AC 100–240 V, 50/60 Hz
<b>Maximum power consumption *8</b>	415 W (4.4–1.8 A) (420 VA)(Power consumption is 400 W at 200–240 V) (TBD)
<b>On-mode power consumption(Operating mode) -&gt; Normal *8 *9</b>	[NORMAL]380 W (100–240 V), 365 W (200–240 V) (TBD)
<b>On-mode power consumption(Operating mode) -&gt; Eco *8 *9</b>	[ECO]275 W (100–240 V), 265 W (200–240 V) (TBD)
<b>On-mode power consumption(Operating mode) -&gt; Quiet *9 *10</b>	[QUIET1]320 W (100–240 V), 310 W (200–240 V) (TBD) [QUIET2]270 W (100–240 V), 260 W (200–240 V) (TBD)
<b>Cabinet materials</b>	Molded plastic
<b>Filter</b>	Included (Estimated maintenance time: approx. 20,000 hours)
<b>Operation noise -&gt; Normal *3</b>	39 dB [NORMAL]
<b>Operation noise -&gt; Eco *3</b>	39 dB [ECO]
<b>Operation noise -&gt; Quiet *3</b>	34 dB [QUIET1] 29 dB [QUIET2]
<b>Dimensions (W x H x D)</b>	399 x 115 x 348 mm (15 23/32" x 4 17/32" x 13 11/16" ) (Excluding protruding parts) (TBD) 399 x 133 x 348 mm (15 23/32" x 5 1/4" x 13 11/16" ) (With legs at shortest position) (TBD)
<b>Weight *10</b>	Approx. 7.6 kg (16.7 lbs) (TBD)
<b>Operating environment -&gt; Operating temperature</b>	0–45 °C (32–113 °F)
<b>Operating Environment -&gt; Operating humidity (No condensation)</b>	20–80 % (No condensation)
<b>Applicable software</b>	Multi Monitoring & Control Software, Presenter Light Software for Windows®*18, Wireless Projector App for iOS/Android™*19

---

**Footnote Description**

1. When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL].
2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.
3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.
4. Average light-output value of all shipped products measured at the center of screen in NORMAL Mode.
5. Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2]). Estimated time until light output declines to 50 % varies depending on environment.
6. Displayed resolution (3840 x 2400 pixels) with 2-axis pixel-shifting technology [ON].
7. Resolution decreases when using Digital Zoom Extender. Grid Adjustment, 6-Point Screen Correction, V/H Keystone Correction, and curved-screen correction are not available when using this function. The range of corner adjustment is limited.
8. When Digital Zoom Extender is set to 80 %.
9. Depending on the connected CEC command compatible device, the link control may not operate normally.
10. YPBPR 4:2:0 format only for 4K/60p signals input via DIGITAL LINK.
11. On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready.
12. The optional AJ-WM50 Series Wireless Module does not support IPv6.
13. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).
14. Filter cleaning cycle varies depending on the environment. The filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m<sup>3</sup>), 10,000 hours (under dust conditions of 0.15 mg/m<sup>3</sup>).
15. Average value. May differ depending on the actual unit.
16. Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level.
17. When the optional AJ-WM50 Series Wireless Module is attached, the operating temperature range becomes 0–40 °C (32–104 °F).
18. When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy while images and sound are being transmitted.
19. When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).