

PT-MZ882 Series - Slant Left Featured Images (Local)


PT-MZ882

PT-MZ882(8,200 lm11), PT-MZ782(7,500 lm11), PT-MZ682(6,500
lm) WUXGA , Multi-Laser Drive Engine
,*1 , ISO/IEC 21118:
2020 .


Key Features



UX

 Geo Pro Logo JPEG



 247 Operation Logo
PNG



Projector type	LCD projector
Display method	Transparent LCD panel (x 3, R/G/B)
Display Device -> Panel size	19.3 mm (0.76 in) diagonal (16:10 aspect ratio)
Display Device -> Drive method	Active matrix method
Display Device -> Number of pixels	2,304,000 (1920 x 1200 pixels)
Light source	Laser diodes
Light output *1 *2	8,200 lm
Light output (ANSI) *1 *3	8,200 lm
Time until light output declines to 50 % *20,000 [NORMAL] -> NORMAL *5	
Time until light output declines to 50 % *24,000 [ECO] -> ECO *5	
Time until light output declines to 50 % *20,000 hours [QUIET] -> QUIET *5	
Resolution *6	WUXGA (1920 x 1200 pixels)
Contrast Ratio (typ.)	3,000,000:1 (Full On/Full Off)(When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1] or [2]. HDMI™ ◆)
Screen size (diagonal)	1.02–10.16 m (40–400 in), 1.52–10.16 m (60–400 in) with the ET-ELW22, 2.54–10.16 m (100–400 in) with the ET-ELU20, 16:10 aspect ratio
Center-to-corner zone ratio	85%
Lens	Powered zoom (throw ratio 1.61–2.76:1), powered focus F = 1.7–2.3, f = 26.8–45.5 mm (for supplied lens; optional lenses also available)
Lens shift -> Vertical(from center of screen)	±67 % (powered), ±60 % (with ET-ELW22), ±50 % (with ET-ELU20) (TBD)
Lens shift -> Horizontal(from center of screen)	±35 % (powered), ±30 % (with ET-ELW22), ±24 % (with ET-ELU20) (TBD)
Keystone correction range	Vertical: ±25 ° (±22 ° with ET-ELW21/ET-ELW22); (±25 ° with ET-ELW20/ET-ELT22/ET-ELT23); (±5 ° with ET-ELU20), Horizontal: ±30 ° (±15 ° with ET-ELW21/ET-ELW22); (±30 ° with ET-ELW20/ET-ELT22/ET-ELT23); (0 ° with ET-ELU20)
Installation	/ , / , 360
Terminals -> HDMI™ IN	HDMI™ x 3 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input*4), CEC supported
Terminals -> COMPUTER IN (D-SUB 15pin)	D- HD 15 (female) x 1 (RGB/YP _{Bp} /YC _{BcR})
Terminals -> COMPUTER OUT (D-SUB 15pin)	D- HD 15 (female) x 1 (RGB/YP _{Bp} /YC _{BcR})
Terminals -> AUDIO IN(M3 Stereo Mini Jack)	M3 stereo mini-jack x 1
Terminals -> AUDIO OUT(M3 Stereo Mini Jack)	M3 stereo mini-jack x 1
Terminals -> MULTI PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> MULTI PROJECTOR SYNC OUT	D-sub 9-pin (male) x 1 for link control
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> SERIAL/MULTI-PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> SERIAL/MULTI-PROJECTOR SYNC OUT	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
Terminals -> REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals -> DIGITAL LINK IN / LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p*4 *5 signal input)
Terminals -> LAN	RJ-45 x 1 , 10Base-T, 100Base-TX (PLink™ [Class 2], Art-Net)
Terminals -> DC OUT	USB Type A x 1 (for power supply, DC 5 V, 2 A)
Power supply	AC 100–240 V, 50 Hz/60 Hz
Maximum power consumption *13	465 W (5.1–2.5 A) (490 VA)(Power consumption is 445 W at AC 200–240 V) (TBD)
On-mode power consumption(Operating mode) -> Normal *13 *14	[NORMAL] 410 W (AC 100–120 V), 390 W (AC 200–240 V) (TBD)
On-mode power consumption(Operating mode) -> Eco *13 *14	[ECO] 295 W (AC 100–120 V), 280 W (AC 200–240 V) (TBD)
On-mode power consumption(Operating mode) -> Quiet *13 *14	[QUIET] 290 W (AC 100–120 V), 275 W (AC 200–240 V) (TBD)
Cabinet materials	Molded plastic
Filter *15	Included
Estimated filter maintenance cycle	20,000
Operation noise -> Normal	34 dB [NORMAL]
Operation noise -> Eco	34 dB [ECO]
Operation noise -> Quiet	26 dB [QUIET]
Body Colour	PT-MZ882BE-BlackPT-MZ882B-BlackPT-MZ882WEJ-WhitePT-MZ882W-WhitePT-MZ882WD8-White
Dimensions (W x H x D)	561 × 224 × 439 mm (22 3/32" × 8 13/16" × 17 9/32") (,)

Dimensions -> Width (including protruding parts)	561 mm (22 3/32")
Dimensions -> Height (including protruding parts)	224 mm (8 13/16")
Dimensions -> Depth (including lens)	439 mm (17 9/32")
Gross Dimensions (W x H x D in mm)	MZ882WEJ/MZ882BEJ/MZ882WU7/MZ882BU7: 756 x 545 x 348 mm MZ882W/MZ882B: 746 x 535 x 332 mm
Weight *16	18.6 kg (41.0 lbs) ()
Gross Weight (Kg)	MZ882WEJ/MZ882BEJ: 24.5 kg (54.0 lbs) MZ882W/MZ882B: 23.0 kg (50.8 lbs)
Operating environment -> Operating temperature *17 *18	0-45 °C (32-113 °F)
Operating Environment -> Operating humidity (No condensation)	10-80 % (no condensation)
Applicable software	Geometry Manager Pro*9, iOS/Android™
NFC	No
EAN	MZ882WEJ: 5025232963867 MZ882BEJ: 5025232963881 MZ882W: 5025232963874 MZ882B: 5025232963898
Terminals -> SDI IN	—
Terminals -> DVI-D IN	—
Terminals -> DisplayPort™ IN	—
Active 3D	No
SDM	No
Footnote Description	<p>1. [PICTURE MODE]가 [DYNAMIC] [LIGHT POWER]가 [NORMAL]</p> <p>2. ISO/IEC 21118: 2020</p> <p>3. (American National Standards Institute)</p> <p>4. 50% ((PICTURE MODE): [DYNAMIC], [DYNAMIC CONTRAST] [2]). 50 %</p> <p>5. 4K (1920 x 1200 pixels)</p> <p>6. YPbPr 4K/60p 4K/50p 4:2:0</p> <p>7. ISO/IEC 21118: 2020 .ON 25 °C(77 °F), 700 m(2,297 ft)</p> <p>8.</p> <p>9. 2,700 m(8,858 ft) : 700 m(2,297 ft) 36 °C(97 °F) 700 m(2,297 ft) 1,400 m(4,593 ft) 34 °C(93 °F) 1,400 m(4,593 ft) 2,100 m(6,890 ft) 32 °C(90 °F) 2,100 m(6,890 ft) 2,700 m(8,858 ft) 30 °C(86 °F)</p> <p>10. Geo Pro</p>