



PT-MZ782

PT-MZ882(8,200 lm11), PT-MZ782(7,500 lm11), PT-MZ682(6,500 lm) WUXGA , Multi-Laser Drive Engine , . *1 , ISO/IEC 21118: 2020 .

Key Features

UX



PT-MZ782

<https://ap.pnd.panasonic.com/sg/ko/pt-mz782>

Projector type	LCD projector
Display method	Transparent LCD panel (x 3, R/G/B)
Display Device -> Panel size	19.3 mm (0.76 in) diagonal (16:10 aspect ratio)
Display Device -> Drive method	Active matrix method
Display Device -> Number of pixels	2,304,000 (1920 x 1200 pixels)
Light source	Laser diodes
Light output *1 *2 *3	7,500 lm
Light output (ANSI) *1 *2 *4	7,500 lm
Time until light output declines to 50 % -> NORMAL *6	20,000 [NORMAL]
Time until light output declines to 50 % -> ECO *6	24,000 [ECO]
Time until light output declines to 50 % -> QUIET *5	20,000 hours [QUIET]
Resolution	WUXGA (1920 x 1200 pixels)
Contrast Ratio (typ.) *3	3,000,000:1 (Full On/Full Off)(When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1] or [2]. HDMI™ ())
Screen size (diagonal)	1.02-10.16 m (40-400 in), 1.52-10.16 m (60-400 in) with the ET-ELW22, 2.54-10.16 m (100-400 in) with the ET-ELU20, 16:10 aspect ratio
Center-to-corner zone ratio *3	85%
Lens	Powered zoom (throw ratio 1.61-2.76:1), powered focus F = 1.7-2.3, f = 26.8-45.5 mm (for supplied lens; optional lenses also available)
Lens shift -> Vertical(from center of screen)	±67 % (powered), ±60 % (with ET-ELW22), ±50 % (with ET-ELU20) (TBD)
Lens shift -> Horizontal(from center of screen)	±35 % (powered), ±30 % (with ET-ELW22), ±24 % (with ET-ELU20) (TBD)
Keystone correction range	Vertical: ±25 ° (±22 ° with ET-ELW21/ET-ELW22); (±25 ° with ET-ELW20/ET-ELT22/ET-ELT23); (±5 ° with ET-ELU20), Horizontal: ±30 ° (±15 ° with ET-ELW21/ET-ELW22); (±30 ° with ET-ELW20/ET-ELT22/ET-ELT23); (0 ° with ET-ELU20)
Installation	/ , / , 360
Terminals -> HDMI™ IN	HDMI™ x 3 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input*4), CEC supported
Terminals -> COMPUTER IN (D-SUB 15pin)	D-sub HD 15-pin (female) x 1(RGB/YPbPr/YCbCr)
Terminals -> COMPUTER OUT (D-SUB 15pin)	D-sub HD 15-pin (female) x 1(RGB/YPbPr/YCbCr)
Terminals -> AUDIO IN(M3 Stereo Mini Jack)	M3 stereo mini-jack x 1
Terminals -> AUDIO OUT(M3 Stereo Mini Jack)	M3 stereo mini-jack x 1
Terminals -> MULTI PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> MULTI PROJECTOR SYNC OUT	D-sub 9-pin (male) x 1 for link control
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> SERIAL/MULTI-PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> SERIAL/MULTI-PROJECTOR SYNC OUT	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
Terminals -> REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
Terminals -> REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals -> DIGITAL LINK IN / LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBaseT™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p*4 *5 signal input)
Terminals -> LAN	RJ-45 x 1 , 10Base-T, 100Base-TX (PLink™ [Class 2], Art-Net)
Terminals -> DC OUT	USB Type A x 1 (for power supply, DC 5 V, 2 A)
Power supply	AC 100-240 V, 50 Hz/60 Hz
Maximum power consumption *9	428 W (4.7-2.3 A) (450 VA)(Power consumption is 408 W at AC 200-240 V) (TBD)
On-mode power consumption(Operating mode) > Normal *9 *9 *10	[NORMAL] 385 W (AC 100-120 V), 365W (AC 200-240 V) (TBD)
On-mode power consumption(Operating mode) > Eco *9 *9 *10	[ECO] 280 W (AC 100-120 V), 270 W (AC 200-240 V) (TBD)
On-mode power consumption(Operating mode) > Quiet *13 *14	[QUIET] 275 W (AC 100-120 V), 265 W (AC 200-240 V) (TBD)
Cabinet materials	Molded plastic
Filter	Included
Estimated filter maintenance cycle	20,000
Operation noise -> Normal *3	32 dB [NORMAL]
Operation noise -> Eco *3	32 dB [ECO]
Operation noise -> Quiet	26 dB [QUIET]
Body Colour	PT-MZ782BEJ-BlackPT-MZ782B-BlackPT-MZ782WEJ-WhitePT-MZ782W-WhitePT-MZ782WD8-White

Dimensions (W x H x D)	561 × 224 × 439 mm (22 3/32" × 8 13/16" × 17 9/32") (,)
Dimensions -> Width (including protruding parts)	561 mm (22 3/32")
Dimensions -> Height (including protruding parts)	224 mm (8 13/16")
Dimensions -> Depth (including lens)	439 mm (17 9/32")
Gross Dimensions (W x H x D in mm)	MZ782WEJ/MZ782BEJ/MZ782WU7/MZ782BU7: 756 x 545 x 348 mm MZ782W/MZ782B: 746 x 535 x 332 mm
Weight *11	18.6 kg (41.0 lbs) ()
Gross Weight (Kg)	MZ782WEJ/MZ782BEJ: 24.5 kg (54.0 lbs) MZ782W/MZ782B: 23.0 kg (50.8 lbs)
Operating environment -> Operating temperature *12	0-45 °C (32-113 °F)
Operating Environment -> Operating humidity (No condensation)	10-80 % (no condensation)
Applicable software	, , , iOS/Android™ , Geometry Manager Pro*9
NFC	No
EAN	MZ782WEJ: 5025232963904 MZ782BEJ: 5025232963928 MZ782W: 5025232963911 MZ782B: 5025232966852
Terminals -> SDI IN	—
Terminals -> DVI-D IN	—
Terminals -> DisplayPort™ IN	—
Active 3D	No
SDM	No
Light output (Center) *1 *2 *5	7,800 lm*4
Footnote Description	1. [PICTURE MODE]가 [DYNAMIC] [LIGHT POWER]가 [NORMAL] 2. , , ISO/IEC 21118: 2020 3. , , (American National Standards Institute) 4. 50% . ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] [2]). 50 % 5. 4K (1920 x 1200 pixels) 6. YP _B P _R 4K/60p 4K/50p 4:2:0 7. , , ISO/IEC 21118: 2020 . ON 25 °C(77 °F), 700 m(2,297 ft) 8. 9. 2,700 m(8,858 ft) : 700 m(2,297 ft) 36 °C(97 °F) , 700 m(2,297 ft) 1,400 m(4,593 ft) 가 34 °C(93 °F) , 1,400 m(4,593 ft) 2,100 m(6,890 ft) 32 °C(90 °F) , 2,100 m(6,890 ft) 2,700 m(8,858 ft) 30 °C(86 °F) 10. Geo Pro