

# Panasonic



## ET-FMP50

Key Features

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_



## ET-FMP50

<https://ap.pnd.panasonic.com/th/ko/ET-FMP50>

<b>Type</b>	◆
<b>Terminals -&gt; HDMI™ IN</b>	—
<b>Terminals -&gt; HDMI™ OUT</b>	HDMI™ x 4, Audio signal: Linear PCM, 44.1 kHz/48 kHz, 16-bit, 2 channels
<b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>	3.5 mm stereo mini-jack
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T,NDI® and Dante® (2 channels)*1 compatible
<b>Video format</b>	HAP*3 / H.264, 8-bit, 3840 x 2160 pixels, 60p, YPbPr 4:2:0, 300 Mbps / H.265, 8-bit, 18 million pixels (long side 7680 pixels or less), 60p, (including 7680 x 1920/60p, 4096 x 4096/60p), YPbPr 4:2:0, 300 Mbps
<b>Max. video output resolution</b>	3840 x 2160/60p x 1    1920 x 1080/60p x 4*2
<b>Audio format</b>	AAC-LC, 16-bit, ◆
<b>Storage</b>	4 TB
<b>Operating system</b>	◆ ®
<b>Power supply</b>	AC 100–240 V, 50/60 Hz
<b>Maximum power consumption</b>	64 W
<b>Dimensions (W x H x D)</b>	210 x 44 x 295 mm (8 9/32" x 1 23/32" x 11 5/8") ( )
<b>Weight</b>	2.0kg(4.41 ) (AC )
<b>ENVIRONMENT -&gt; Operating Environment(Temperature)</b>	0–40 °C (32–104 °F)
<b>ENVIRONMENT -&gt; Operating Environment(Humidity) (No condensation)</b>	10–80 % (no condensation)
<b>Accessory Type</b>	Media Processor
<b>Applicable projectors</b>	All Projector
<b>Footnote Description</b>	<ol style="list-style-type: none"> <li>1. HAP Q ◆</li> <li>2. HDMI™ 4</li> <li>3. HAP 1 HAP Q</li> <li>4. ET-FMP20(512 GB) ET-SBFMP10(512 GB) 30 GB가 ◆</li> <li>5. ET-SBFMP10</li> </ol>