

Panasonic



• 8,000 lm*1

PT-VMZ82

VMZ82 : 1 8,000 lm2 ,
LCD VMZ82
, Panasonic
, VMZ82

Key Features

-
-
-



PT-VMZ82

<https://ap.pnd.panasonic.com/vn/ko/pt-VMz82>

Projector type	LCD projectors		
Display method	Transparent LCD panel (x 3, R/G/B)		
Display Device -> Panel size	16.3 mm (0.64 inch) (16:10 aspect ratio)		
Display Device -> Number of pixels	2,304,000 (1920 x 1200) pixels x 3		
Light source	Laser diodes		
Light output *1 *2 *3	VMZ82 : 8,000 lm*2 VMZ72 : 7,200 lm*2 VMZ62 : 6,500 lm*2		
Light output (ANSI) *1 *2 *4	VMZ82 : 8,000 lm (ANSI)*3 VMZ72 : 7,200 lm (ANSI)*3 VMZ62 : 6,500 lm (ANSI)*3		
Time until light output declines to 50 % -> NORMAL *6	20,000	[NORMAL]	
Time until light output declines to 50 % -> ECO *6	24,000	[ECO]	
Time until light output declines to 50 % -> QUIET *5	20,000 hours	[QUIET]	
Resolution	WUXGA (1920 x 1200 pixels)		
Contrast Ratio (typ.) *3	5,000,000:1 (Full On/Full Off) ([PICTURE MODE]가 [DYNAMIC CONTRAST]가 [1] .)	[DYNAMIC]	
Screen size (diagonal)	0.76~7.62 m (30~300 in), 16:10 aspect ratio		
Center-to-corner zone ratio *3	85 %		
Lens	1.6x manual zoom (throw ratio: 1.09~1.77:1), manual focus lens, F=1.58-1.91, f=15.30~24.60 mm		
Digital Zoom Extender *7	1.09-2.21:1*6 (. .)		
Lens shift -> Vertical(from center of screen)	+44 %		
Lens shift -> Horizontal(from center of screen)	±20%		
Keystone correction range	±25°, ±35°		
Terminals -> HDMI™ IN	HDMI™ 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/30p*8 signal input), CEC supported*9		
Terminals -> COMPUTER IN (D-SUB 15pin)	D-sub 15-pin (female) (RGB/YpBpR/YcBcR)		
Terminals -> AUDIO IN(M3 Stereo Mini Jack)	M3 stereo mini-jack x 1		
Terminals -> AUDIO OUT(M3 Stereo Mini Jack)	M3 stereo mini-jack x 1		
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)		
Terminals -> DIGITAL LINK IN / LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBaseT™ compliant), 100Base-TX (Compatible with PLink™ [Class 2],HDCP, Deep Color, 4K/30p*7 signal input)		
Terminals -> LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PLink™[Class 2]		
Terminals -> USB TYPE A	USB A x 1	AJ-WM50	(DC 5 V, 2 A*9)
Protocol versions	IPv4, IPv6*10		
Power supply	AC 100-240 V, 50/60 Hz		
Maximum power consumption *9	400 W (4.2 A) (405 VA) (Power consumption is 385 W at 200-240 V)		
On-mode power consumption(Operating mode) -> Normal *9 *9 *10	365 W (100-240 V), 350 W (200-240 V) [NORMAL]		
On-mode power consumption(Operating mode) -> Eco *9 *9 *10	260 W (100-240 V), 250 W (200-240 V) [ECO]		
On-mode power consumption(Operating mode) -> Quiet *13 *14	305 W (100-240 V), 295 W (200-240 V) [QUIET1] 255 W (100-240 V), 245 W (200-240 V) [QUIET2]		
Built-in speaker	10 W monaural		
Cabinet materials	Molded plastic		
Filter	Included		
Estimated filter maintenance cycle	20,000		
Operation noise -> Normal *3	39 dB [NORMAL]		
Operation noise -> Eco *3	39 dB [ECO]		
Operation noise -> Quiet	34 dB [QUIET1] 29 dB [QUIET2]		

Dimensions (W x H x D)	399 mm x 115 mm x 348 mm (15 23/32" x 4 17/32" x 13 11/16") () 399 mm x 133 mm x 348 mm (15 23/32" x 5 1/4" x 13 11/16") (가)		
Weight *11	Approx. 7.4 kg (16.3 lbs)		
Operating environment -> Operating temperature *12	0-45 °C (32-113 °F)*14, *15		
Operating Environment -> Operating humidity (No condensation)	20-80 % (no condensation)		
Applicable software	iOS/Android , *17 , Windows® *16 ,		
Terminals -> SDI IN	—		
Terminals -> DVI-D IN	—		
Terminals -> DisplayPort™ IN	—		
Body Colour	PT-VMZ82-WhitePT-VMZ82EJ-WhitePT-VMZ82B-BlackPT-VMZ82BEJ-BlackPT-VMZ82J-WhitePT-VMZ82D8-White		
Gross Dimensions (W x H x D in mm)	VMZ82/VMZ82B/VMZ82J/VMZ82D8: Approx. 538 x 260 x 466 mm VMZ82EJ/VMZ82BEJ: Approx. 546 x 276 x 474 mm		
Gross Weight (Kg)	VMZ82/VMZ82B: 11.0 kg (24.2 lbs)VMZ82J: 10.2 kg (22.5 lbs)VMZ82D8: 11.5 kg (25.4 lbs)VMZ82EJ/VMZ82BEJ: 12.0 kg (26.4 lbs)		
NFC	No		
Active 3D	No		
SDM	No		
EAN	PT-VMZ82: 5025232969845 PT-VMZ82EJ: 5025232969258 PT-VMZ82B: 5025232969272 PT-VMZ82BEJ: 5025232969265 PT-VMZ82D8: 8887549898907		
Footnote Description	1. [PICTURE MODE]가 [DYNAMIC] [LIGHT POWER]가 [NORMAL] 2. , , ISO/IEC 21118: 2020 3. , (American National Standards Institute) 4. 50% . ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] [2]). 50 % 5. Digital Zoom Extender Grid Adjustment, 6-Point Screen Correction, V/H Keystone Correction 6. Digital Zoom Extender 80 % 7. 4K 8. CEC 9. Quick Startup ON Power Management Ready 가 10. AJ-WM50 IPv6 11. , ISO/IEC 21118: 2020 . ON 25 °C(77 °F), 700 m(2,297 ft) 12. 20,000 (0.08 mg/m3), 10,000 (0.15 mg/m3). 13. 14. 30 °C(86 °F) , 2,700 m(8,858 ft) 15. AJ-WM50 0-40 °C(32-104 °F)가 16. Presenter Light Software 1280 × 800 1024 × 768 PC 17. iOS/Android™ WXGA(1280 × 800)		