



**Revitalize Communication with 4,000-lm-class  
XGA Portable Laser Projectors**

## **PT-LMX460**

4,000-lm-class SOLID SHINE Laser Projectors Revitalize  
Communication with WUXGA Images

### **Key Features**

---

Effortless Projection Anywhere, Anytime

---

Efficient, Reliable, and Cost-Effective

---

SOLID SHINE for Clear Images in Bright Light



## PT-LMX460

<https://ap.pnd.panasonic.com/vn/vi/products/projectors/pt-lmx460>

|   |  |
|---|--|
| <b>Projector type</b>   | LCD projectors   |
| <b>Display method</b>   | Transparent LCD panel (x 3, R/G/B)   |
| <b>Display Device -&gt; Panel size</b>                          | 16.0 mm (0.63 in) diagonal (4:3 aspect ratio)  |
| <b>Display Device -&gt; Drive method</b>                        | Active matrix method   |
| <b>Display Device -&gt; Number of pixels</b>                    | 786,432 (1024 x 768) pixels  |
| <b>Light source</b>   | Laser diodes   |
| <b>Light output *1</b>  | 4,600 lm   |
| <b>Light output (ANSI)</b>                                      | 4,600 lm   |
| <b>Time until light output declines to 50 % -&gt; NORMAL *3</b> | 20,000 hours [NORMAL]  |
| <b>Time until light output declines to 50 % -&gt; ECO *3</b>    | 24,000 hours [ECO]   |
| <b>Time until light output declines to 50 % -&gt; QUIET *4</b>  | 20,000 hours [QUIET]   |
| <b>Resolution</b>   | XGA (1024 x 768 pixels)  |
| <b>Contrast Ratio (typ.) *1</b>                                 | 3,000,000:1 (Full On/Full Off)(When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)                        |
| <b>Screen size (diagonal)</b>                                   | 0.76-7.62 m (30-300 in), 4:3 aspect ratio  |
| <b>Center-to-corner zone ratio *1</b>                           | 85%  |
| <b>Lens</b>   | 1.2x manual zoom (throw ratio: 1.47-1.77:1), manual focus lens, F 1.61-1.76, f 19.1-23.0 mm  |
| <b>Digital Zoom Extender *5</b>                                 | Throw ratio: 1.47-2.22:1*5 (Corresponding value. When used together with optical zoom.)  |
| <b>Keystone correction range</b>                                | Vertical: ±35 ° (Auto, Manual),<br>Horizontal: ±35 ° (Manual)  |
| <b>Installation</b>   | Ceiling/floor, front/rear, free 360-degree installation  |
| <b>Terminals -&gt; HDMI™ IN</b>                                 | HDMI™ 19-pin x 2 (Compatible with HDCP 1.4, Deep Color, 4K/30p*6 signal input), CEC supported*7                                      |
| <b>Terminals -&gt; COMPUTER IN ( D-SUB 15pin )</b>              | D-sub 15-pin (female) x 1 (RGB/Y/P <sub>B</sub> /R/YC <sub>B</sub> /C <sub>R</sub> )   |
| <b>Terminals -&gt; COMPUTER OUT ( D-SUB 15pin )</b>             | D-sub 15-pin (female) x 1 (RGB/Y/P <sub>B</sub> /R/YC <sub>B</sub> /C <sub>R</sub> )   |
| <b>Terminals -&gt; AUDIO IN(M3 Stereo Mini Jack)</b>            | M3 stereo mini-jack x 2  |
| <b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>           | M3 stereo mini-jack x 1  |
| <b>Terminals -&gt; SERIAL IN</b>                                | D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)  |
| <b>Terminals -&gt; LAN</b>                                      | RJ-45 x 1 for network control, 10Base-T, 100Base-TX  |
| <b>Terminals -&gt; USB TYPE A</b>                               | USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A*8) |
| <b>Protocol versions</b>  | IPv4, IPv6*9   |
| <b>Power supply</b>   | AC 100 V-240 V, 50/60 Hz   |
| <b>Maximum power consumption</b>                                | 230 W  |
| <b>On-mode power consumption(Operating mode) -&gt; Normal</b>   | [NORMAL]<br>->205 W (100-240 V),<br>195 W (200-240 V)  |
| <b>On-mode power consumption(Operating mode) -&gt; Eco</b>      | [ECO]<br>->155 W (100-240 V),<br>145 W (200-240 V)   |
| <b>On-mode power consumption(Operating mode) -&gt; Quiet *7</b> | [QUIET]<br>->150 W (100-240 V),<br>145 W (200-240 V)   |
| <b>Built-in speaker</b>   | 10 W monaural  |
| <b>Cabinet materials</b>  | Molded plastic   |
| <b>Filter</b>   | Included   |
| <b>Estimated filter maintenance cycle</b>                       | Approx. 20,000 hours   |
| <b>Operation noise -&gt; Normal *1</b>                          | 35 dB [NORMAL]   |
| <b>Operation noise -&gt; Eco *2</b>                             | 35 dB [ECO]  |
| <b>Operation noise -&gt; Quiet *1</b>                           | 24 dB [QUIET]  |
| <b>Body Colour</b>  | White  |
| <b>Dimensions (W x H x D)</b>                                   | 349 mm x 105 mm x 309 mm (13 3/4" x 4 1/8" x 12 5/32" ) (with feet at shortest position)   |
| <b>Dimensions -&gt; Width (including protruding parts)</b>      | 349 mm (13 3/4")   |
| <b>Dimensions -&gt; Height (including protruding parts)</b>     | 105 mm (4 1/8")  |
| <b>Dimensions -&gt; Depth (including lens)</b>                  | 309 mm (12 5/32")  |

|   |   |
|---|---|
| <b>Gross Dimensions (W x H x D in mm)</b>                               | LMX460E: 507 x 402 x 222 mm<br>LMX460: 497 x 392 x 210 mm   |
| <b>Weight *7</b>  | Approx. 4.2 kg (9.26 lbs)   |
| <b>Gross Weight (Kg)</b>  | LMX460E: 7.4 kg(16.3 lbs)<br>LMX460: 6.6 kg(14.6 lbs)   |
| <b>Operating environment -&gt; Operating temperature *8 *9</b>          | 0–45 °C (32–113 °F)   |
| <b>Operating Environment -&gt; Operating humidity (No condensation)</b> | 20–80 % (no condensation)   |
| <b>Applicable software</b>  | Multi Monitoring & Control Software, Projector Network Setup Software, Logo Transfer Software, Presenter Light Software for Windows®*14, Wireless Projector App for iOS/Android™*15   |
| <b>NFC</b>  | <a href="https://docs.connect.panasonic.com/projector/products/smartycontrol/regional.html#regional">https://docs.connect.panasonic.com/projector/products/smartycontrol/regional.html#regional</a>   |
| <b>Control function via LAN</b>   | PJLink™ [Class 2], Crestron Connected™, AMX Device Discovery  |
| <b>EAN</b>  | LMX460: 5025232931606<br>LMX460E: 5025232931613   |
| <b>Footnote Description</b>   | <ol style="list-style-type: none"> <li>1. When [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF], and [AUTO POWER SAVE] is set to [OFF].</li> <li>2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped.</li> <li>3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped.</li> <li>4. Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of particulate matter). Estimated time until light output declines to 50 % varies depending on environment.</li> <li>5. Resolution decreases when using this function. V/H Keystone Correction and curved-screen correction are not available when using this function, and range of corner adjustment is limited.</li> <li>6. When Digital Zoom Extender is set to 80 %.</li> <li>7. 4K signals are converted to the projector's resolution upon projection.</li> <li>8. Depending on the connected CEC command-compatible device, the link control may not operate normally.</li> <li>9. On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready.</li> <li>10. Main projector firmware must be Ver. 2.00 or later. The optional AJ-WM50 Series Wireless Module does not support IPv6.</li> <li>11. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).</li> <li>12. Filter cleaning cycle varies depending on environment. Filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m<sup>3</sup>), 10,000 hours (under dust conditions of 0.15 mg/m<sup>3</sup>).</li> <li>13. Average value. May differ depending on the actual unit.</li> <li>14. Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level. When optional AJ-WM50 Series Wireless Module is attached, operating temperature range becomes 0–40 °C (32–104 °F).</li> <li>15. When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy, while images and sound are being transmitted.</li> <li>16. When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).</li> </ol> |